

# Installation Instructions & Use Recommendations

## FMS Accessories – Radio Head Mounting Bracket

These instructions must be read carefully and thoroughly **before** beginning work. FMS Solutions, LLC accepts no liability for damage caused by failure to observe the installation instructions or use recommendations.

**Installation of this accessory does not change the factory specified load limits for the motorcycle.**

Place a shop rag around the steering head so that when you drop the bolts securing the bracket, they don't fall into a black hole!

Remove the standard factory bracket T25. Keep the bolts, as you will need them for the new radio head mount.



Insert the M6 x 15 self-clinching studs from the underside, temporarily holding them in place with masking tape. Leave a tab so that you can remove the tape later.

There is no room to insert the studs once mounted, so do this first. If a map light is being installed, attach that first as well.

Keep the bracket as light as possible to install, then bolt your Motorola radio head bracket afterward. If the agency is installing it, secure the studs with the M6 flanged nuts provided.



It helps to turn the handlebar to the left when installing the RH screw, and turning the handlebar to the right when installing the LH screw. This is a very tight fit so the more room the easier it is.



Using a T25 in a small driver, tighten the two bolts securing the bracket to the handlebar clamp casting. Press up from the bottom of the T25 bit to achieve ratcheting action while tightening the bolts.



**Feedback:** Thank you for your purchase and we welcome your feedback as we too want to make every accessory exceed your expectations. Report any comments, suggestions, problems or concerns to FMS Solutions, LLC at [info@fmsaccessories.com](mailto:info@fmsaccessories.com).

**FMS Solutions, LLC Limited Warranty**

FMS Solutions, LLC warrants to the first retail purchaser of new FMS Accessory products, to be free from defects in materials or workmanship, for a period of three (3) years from the original date of purchase as noted on the FMS Solutions, LLC invoice or original dealer invoice, except for paint and powder-coated finishes, which are warranted for the first 12 months only. LED lights from Fenix, Inc., Code 3, Inc. and Littlite are covered for 5 years by their manufacturer's respective warranties – processed through FMS Solutions, LLC.

**This warranty extends only to the FMS accessory and does not include:** damage caused by accidents or abuse; incorrect installation; labor to diagnose, remove, repair or replace; any consequential damage or loss of use. Any FMS Accessory suspected of being defective should be returned to FMS Solutions, LLC along with a copy of proof of purchase and warranty request form available on the FMS website. FMS Solutions, LLC will determine if the FMS accessory has a warrantable defect, and if so, will repair or replace the item and return it to the sender without charge. The decision to repair or replace said item is solely the prerogative of FMS Solutions, LLC.

**Note:** Police motors can operate in a very rough environment since police motors are a "tool". They can be dropped, knocked-over, etc. without concern as the officer has a job to do and determines what is necessary at any given moment. Warranty is for defects in materials or workmanship. Therefore, the ability of an item to become broken or damaged does not mean it is warranty ... it just means it is broken or damaged and in need of repair or replacement. No manufacturer warrants their products to be indestructible. Any questions should be directed to [info@fmsaccessories.com](mailto:info@fmsaccessories.com).